



---

**Declaration of Performance (DoP) in acc. with**

**Construction Products (Amendment etc.) (EU Exit) Regulations 2020 (No. 1359)**

**Nr. PTG25-UKCA-10025-14022022**

---

1. Unique identification code of the product type:

**Hot rolled constructional steel products**

2. Type, batch or serial number or any element allowing identification of the construction product:

**Sections made from thermomechanical rolled weldable fine grain structural steel  
EN 10025-4-S460M**

3. Intended use or uses of the construction product in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Welded, bolted and riveted structures**

4. Name, registered trade name or registered trademark and contact address of the manufacturer

**PEINER TRÄGER GmbH,  
Gerhard-Lucas-Meyer-Str. 10,  
31226 Peine, Germany  
+49 5171 91 - 01,  
+49 5171 91 - 92 62,  
www.peiner-traeger.de**

5. Name and contact address of the authorised representative whose mandate covers the tasks:

**- not applicable -**

6. System or systems of assessment and verification of constancy of performance of the construction product:

**System 2+**

7. Declaration of performance concerning a construction product covered by a harmonised standard:

**Approved body – British Board of Agrément (no. 0863) – performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control in accordance with annex ZA of EN 10025-1:2004.**

**8. Declared Performance:**

Essential characteristic	Performance				Harmonised technical specification
<b>Tolerances on dimensions and shape</b>	I- and H- shaped sections see supplementary sheet 1 U-Shapes: see supplementary sheet 2				<b>EN 10025-1:2004</b>
	<b>Nominal thickness (mm)</b>		<b>Values</b> EN 10025-4-S460M		
<b>Yield strength</b>	>	≤	<b>R<sub>eH</sub> (MPa)</b>		
			≥		
	-	16	460		
	16	40	440		
	40	63	430		
	63	80	410		
	80	100	400		
<b>Tensile strength</b>	>	≤	<b>R<sub>m</sub> (MPa)</b>		
			≥	≤	
	-	40	540	720	
	40	63	530	710	
	63	80	510	690	
	80	100	500	680	
<b>Elongation</b>	>	≤	<b>A<sub>5</sub> (%)</b>		
			≥		
	-	100	17		
<b>Impact strength</b>	>	≤	<b>KV (J) -20°C</b>		
			≥		
	-	100	40		
<b>Weldability</b>	>	≤	<b>CEV (%)</b>		
			≤		
	-	16	0,45		
	16	40	0,46		
	40	63	0,47		
	63	100	0,48		
<b>Durability</b>	>	≤	<b>Ladle analysis (%)</b>		
			≥	≤	
	-	100	C: 0,18	V: 0,12	
			Si: 0,60	Ti: 0,05	
			Mn: 1,70	Cr: 0,30	
			P: 0,035	Ni: 0,80	
			S: 0,030	Mo: 0,20	
			Nb: 0,05	Cu: 0,55	
				N: 0,025	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Peine, 14.02.2022


**Marcus Lippe**

Head of technical services and quality department